

Externally Mounted Ignition Coils

With Diagnostic Interface



Ignition Coils
reliable • efficient • worldwide

General Information

Externally Mounted Ignition Coils with Diagnostic Interface

MOTORTECH offers the typical shielded ignition coils (externally as also flange mounted) with an integrated BNC connector. The MOTORTECH SparkView high voltage indicator or a digital scope meter can be hooked up and will read the high voltage demand of the spark plug.

General Features

- Allow an inductively access to the high voltage circuit of the shielded ignition coils
- Offer great advantages to service engineers and operators
- Available with 3 and 2 pole primary termination
- Offered with 3/4-20 UNEF and 1-20 UNEF high voltage termination
- Meet CSA Class I, Division 2, Group C/D




Features

- 1 High voltage termination for spark plug lead connection
 - 3/4-20 UNEF outer thread for ALTRONIC® compatibility
 - 1-20 UNEF outer thread FAIRBANKS MORSE® style
- 2 Nickel plated steel housings with safety belt
- 3 Stainless steel brackets (replaceable)
- 4 Different versions for use with MOTORTECH ignition controllers (support MOST and ASC technology) or to function with the ALTRONIC® patented “Spark Reference” high voltage indication system
- 5 Primary termination for primary lead connection
 - 3 pole MIL style connectors for ALTRONIC® compatibility
 - 2 pole MIL style connectors FAIRBANKS MORSE® style
- 6 Additional BNC connector for high voltage measurement



Ordering Information



SparkView – MOTORTECH High Voltage Indicator

The SparkView is a handheld device developed by MOTORTECH that can monitor the high voltage required by the spark plug while the engine is running. With a BNC cable and the display for up to 40 kV, it is easy to determine the condition of the spark plugs and the time at which they need to be replaced.



Shielded Primary Leads

MOTORTECH primary leads are available as Conventional or New Flex Style that is produced with a special multilayer wire. The new primary leads offer a significant higher flexibility than conventional leads, shielded with braided steel, while being highly resistant to all kinds of environmental conditions. Primary leads are available with rigid terminations in several different configurations with durable 90° and 180° 2 pole and 3 pole connectors.



Shielded Spark Plug Leads

Available in Conventional or MOT-Blues style to replace any product in the market. The MOT-Blues spark plug wire is a MOTORTECH development with a special multilayer design to ensure that no humidity can be trapped in the lead.

3 Pole Primary Connector Arrangement



P/N	Primary Termination	HV Termination	Polarity	MOST	Equivalent to ¹⁾
95.09.070	MIL style, 3 pole, pin	3/4-20 UNEF	(-) ground	x	95.09.005
95.09.073	MIL style, 3 pole, pin	3/4-20 UNEF	(+) ground	Not applicable	291001-S, 95.09.053
95.09.074	MIL style, 3 pole, pin	3/4-20 UNEF	(-) ground	Not applicable	591010-S, 95.09.054
95.09.075	MIL style, 3 pole, pin	3/4-20 UNEF	(-) ground	Not applicable	501061-S, 2881178, 95.09.055

¹⁾ Part numbers indicated for comparison purposes.

2 Pole Primary Connector Arrangement



P/N	Primary Termination	HV Termination	Polarity	MOST	Equivalent to ¹⁾
95.08.070	MIL style, 2 pole, pin	1-20 UNEF	(-) ground	x	PPT2477AD, PPT2477ADL, 95.08.003

¹⁾ Part numbers indicated for comparison purposes.

Download now!



All Products at a Glance!

For further Information about the MOTORTECH products get our product guide online.



Scan QR-Code to get to the download page



Distribution partner for DENSO spark plugs



Scan QR-Code to subscribe



Once a month the latest news!

Subscription also at www.motortech.de/subscribe or send a short request via e-mail: direkt@motortech.de

MOTORTECH GmbH

Hogrevestr. 21-23
29223 Celle
Germany
Phone: +49 (5141) 93 99 0
Fax: +49 (5141) 93 99 99
www.motortech.de
sales@motortech.de

MOTORTECH Americas, LLC

1400 Dealers Avenue, Suite A
New Orleans, LA 70123
USA
Phone: +1 (504) 355 4212
Fax: +1 (504) 355 4217
www.motortechamericas.com
info@motortechamericas.com

MOTORTECH Shanghai Co. Ltd.

Room 1018 Enterprise Square,
No. 228 Meiyuan Road,
Zhabei District, 200070 Shanghai
China
Phone: +86 (21) 6380 7338
www.motortechshanghai.com
info@motortechshanghai.com

P/N 01.15.044-EN | Rev.09/2016 | MOTORTECH Sales Flyer Externally Mounted Ignition Coils

Copyright

The copyright for all materials used in this MOTORTECH publication is reserved. Any kind of duplication or use of objects such as pictures or texts in other electronic or printed publications without approval by MOTORTECH is not permitted.

Trademark Information

MOTORTECH products and the MOTORTECH logo are registered and/or common law trademarks of MOTORTECH GmbH.

All OEM names and part numbers shown are for reference purposes only. All trademarks, logos and symbols used or shown in this MOTORTECH publication are exclusive objects to the right of their owners and are used for reference purposes only.

Distribution: