

Spark Plugs & Accessories

MOTORTECH Spark Plug Cleaning Kit

Regular maintenance is required to achieve the maximum service life in particular with high price spark plugs with precious metal alloys. Apart from readjusting the electrode gap, the spark plug should also be freed from deposits and residues that have formed during operation. By using the MOTORTECH spark plug cleaning kit these can be removed easily and gently in the electrode area and on the thread within a regular maintenance interval. This will increase spark plug service life and cut maintenance costs.

Features

- Professional cleaning of spark plugs without pre-chamber
- Different nozzle sizes matching M18-, M14 and 7/8 inch spark plugs
- Oil residues and deposits in the electrode area are removed without residues by high pressure
- Special blasting grit for gentle cleaning of the electrode and thread area
- Blasting grit is captured and can be reused
- No dust development







MOTORTECH GmbH | Hogrevestr. 21-23 | 29223 Celle | Germany | Phone: +49 5141 93 99 0 | Fax: +49 5141 93 99 99 | www.motortech.de MOTORTECH Americas, LLC | 1400 Dealers Avenue, Suite A | New Orleans | LA 70123 | Phone: +1 504 355 4212 | Fax: +1 504 355 4217 | www.motortechamericas.com

01.25.009-EN REV. 08/2015



Spark Plugs & Accessories

Scope of Delivery

The spark plug cleaning kit is supplied with the following parts:

- Spark plug cleaning device with compressed air quick release coupling, blasting grit container and dust collector bag
- Cleaning nozzles for M14-, M18 and 7/8 inch spark plugs
- Blasting grit, 1 kg, in separate container
- Operating manual
- Hard shell carrying case with foam insert

Technical Data

Dimensions of cleaning device

335 x 106 x 210 mm (L x W x H) (13.2 x 4.2 x 8.3 in)

Weight (without blasting grit)

0.82 kg (1.8 lbs)

Air consumption

- 390 l/min (13.8 cfm) at 6 bar (87 psi) operating pressure
- 420 l/min (14.9 cfm) at 8 bar (116 psi) operating pressure

Operating pressure

6 to 8 bar max. (87 to 116 psi)

Required air quality

purified, oil-free

Power output of the compressor

250 l/min. (8.85 cfm) output or higher, which corresponds with a motor output of 2.5 kW

Recommended hose diameter ■ 6 mm (0.24 in)

Blasting grit container volume 0.7 l (42.72 in³)

Blasting grit grain size

0.2 to 0.8 mm (0.008 to 0.031 in)

Ordering Information

P/N	Description
44.01.023	Spark plug cleaning kit

Ordering Information – Subcomponents

P/N	Description
44.01.009	Blasting grit, 1 kg
44.01.024	Cleaning nozzles, kit for M14-, M18 and 7/8 in spark plugs
44.01.025	Dust collector bag for spark plug cleaning device

Copyright

The copyright for all materials used in this MOTORTECH publication is reserved. Any kind of duplication or use of objects such as pictures or texts in other electronic or printed publications without approval by MOTORTECH is not permitted.

Trademark Information

MOTORTECH products and the MOTORTECH logo are registered and/or common law trademarks of MOTORTECH GmbH.

All OEM names and part numbers shown are for reference purposes only. All trademarks, logos and symbols used or shown in this MOTORTECH publication are exclusive objects to the right of their owners and are used for reference purposes only. Distribution: